



Features

- Time delay (T) IEC127-2/3
- Glass cartridge, nickel plated end caps
- Break capacity 35A/250V or 10 x In whichever is greater at above 3.5A
- Approvals:
SEMKO, VDE, UL and BSI
125mA to 6.3A
- Colour coded available
- Spiral Element or Plated Solder Section for Superior Characteristics
- Axially Centred Element



Glass 5x20mm



Type No.	Rating	Type No.	Rating
CF0520T/32	32mA	CF0520T/800	800mA
CF0520T/40	40mA	CF0520T/1	1A
CF0520T/50	50mA	CF0520T/1.25	1.25A
CF0520T/63	63mA	CF0520T/1.6	1.6A
CF0520T/80	80mA	CF0520T/2	2A
CF0520T/100	100mA	CF0520T/2.5	2.5A
CF0520T/125	125mA	CF0520T/3.15	3.15A
CF0520T/160	160mA	CF0520T/4	4A
CF0520T/200	200mA	CF0520T/5	5A
CF0520T/250	250mA	CF0520T/6.3	6.3A
CF0520T/315	315mA	CF0520T/8	8A
CF0520T/400	400mA	CF0520T/10	10A
CF0520T/500	500mA	CF0520T/12.5	12.5A
CF0520T/630	630mA		