


# QUICK DISCONNECTS

## Female Spade Disconnects



- **Material**
- Insulation: Vinyl
- Terminal Body: Brass
- Metallic Sleeve: Copper
- Plating: Tin



## Female Spade Disconnects

WIRE RANGE mm <sup>2</sup> (A.W.G.)	TAB SIZE Thickness × Width	ITEM NO .	DIMENSION mm(inch)				COLOUR
			W	L	B	C	
0.5-1.5 (22-16)	0.5×2.8 .020×.110	RFS28-5	3.2(.126)	19.0(.748)	10.5(.413)	1.7(.067)	
	0.8×2.8 .032×.110	RFS28-8	3.2(.126)				
	0.5×4.75 .020×.187	RFS48-5	5.0(.197)	19.4(.764)			
	0.8×4.75 .032×.187	RFS48-8	5.0(.197)				
	0.8×6.35 .032×.250	RFS63	6.6(.260)	20.8(.819)			
1.5-2.5 (16-14)	0.5×4.75 .020×.187	BFS48-5	5.0(.197)	19.4(.764)	10.5(.413)	2.3(.091)	
	0.8×4.75 .032×.187	BFS48-8	5.0(.197)				
	0.8×6.35 .032×.250	BFS63	6.6(.260)	20.8(.819)			
	0.8×8.0 .032×.312	BFS83	8.2(.323)	24.5(.965)			
4-6 (12-10)	0.8×6.35 .032×.250	YFS63	6.6(.260)	23.3(.917)	13.0(.512)	3.4(.134)	
	1.2×9.4 .047×.375	YFS95	10.0(.394)	28.6(1.126)			