



Recommended P.C.B Layout

MATERIAL

Insulator : Nylon 66 UL 94V-2
Contact Pin : Brass

SPECIFICATION

Current Rate : 5 AMP
Dielectric voltage : 250V(AC)
Insulation Resistance : 1000MΩMin
Contact Resistance : 20mΩMax
Operation Temperature : -25°C to +85°C

759-71-xx T W 0 1
1 2 3 4 5

- 1. 5: Normal parts
- 7: Green Product
- 9: Green Product High Temp
- 2. No. of contacts per row
- 3. G: Gold flash
- S: Selective
- T: Tin plated
- 4. S: Crystal insulator
- W: White insulator
- 5. Pinrex internal code.

Poles	DIM A	DIM B
2	5.08	10.22
3	10.16	15.30
4	15.24	20.38
5	20.32	25.46
6	25.40	30.54
7	30.48	35.62
8	35.56	40.70
9	40.64	45.78
10	45.72	50.86

		TOLERANCE		OLD PART NO. 5083SA-xxTW		TITLE		頻銳科技股份有限公司 PINREX TECHNOLOGY CORP.
		.0 =±.30 .00 =±.20 .000 =±.XXX .0000=±. ANG.=±3'		UNITS : mm		5.08mm WIRE TO BOARD HEADER DIP 180° TYPE		
A	RELEASE	2006/03/17		SCALE	SIZE	SHEET	REV.	NEW PART NO.
REV.	DESCRIPTION	DATE		NONE	A4	1 OF 1	A	759-71-xxTW01
						APP'D		DRAW NO.
								759-71-xxTW01