



Material And Finish

Insulator : PBT&Glass-fibe reinforced UL94V-0
 Contact : Phosphor Bronze or Brass
 Contact Plating : See Contact Plating Tab

SPECIFICATION

Current Rate : 1 AMP
 Contact Resistance : 30mΩMax.at 6V DC 0.3A
 Insulation Resistance : 1000MΩMin. at 500V DC
 Withstanding Voltage : 500V AC/Minute

$$977-11-xx \frac{x}{1} \frac{x}{2} \frac{x}{3} \frac{x}{4} \frac{2}{5}$$

1. No. of contacts per row
2. 1: With Bump
2: Without Bump
3: With Bump (GP)
4: Without Bump(GP)
3. 1: With SR Dual contact
2: Without SR Dual contact
3: With SR Dual contact (GP)
7: With SR Single contact (GP)
4. 0: Selective/Black
1: Selective/Gray
2: Gold flash/Black
5. Pinrex internal code.

No.	A	B	C	D	No.	A	B	C	D
06	12.30	5.08	6.35	3.80/1.80	26	37.70	30.48	31.75	3.80
08	14.84	7.62	8.89	3.80/1.80	30	42.78	35.56	36.83	3.80
10	17.38	10.16	11.43	3.80	34	47.86	40.64	41.91	3.80
12	19.92	12.70	13.97	3.80	36	50.40	43.18	44.45	3.80
14	22.46	15.24	16.51	3.80	40	55.48	48.26	49.53	3.80
16	25.00	17.78	19.05	3.80	50	68.18	60.96	62.23	3.80
18	27.54	20.32	21.59	3.80	60	80.88	73.66	74.93	3.80
20	30.08	22.86	24.13	3.80	64	85.96	78.74	80.01	3.80
24	35.16	27.94	29.21	3.80					

				TOLERANCE		OLD PART NO. UNITS : mm		TITLE		頻銳科技股份有限公司 PINREX TECHNOLOGY CORP.
				.0 =±.30 .00 =±.20 .000 =±.XXX .0000=±. ANG.=±3'		DRAWER 胡雨婷 CHECK		2.54mm Pitch IDC Series		
A	RELEASE	2014/06/14		SCALE NONE	SIZE A4	SHEET 1 OF 1	REV. A	APP'D	NEW PART NO. 977-11-xxxxx2	DRAW NO. 977-11-xxxxx2
REV.	DESCRIPTION	DATE								