

Part Number: PRM-SA-003 (Alternate Part No: S1938)
Aluminium Housed Magnet
Product Data Sheet

PICTURE



✓ **RoHS Compliant**


APPLICATIONS

- Position and limit sensing.
- Machinery safety guard.
- Automated production line.
- Security alarm system.

OPTIONS

- Robust sealed magnet.
- Powder coated to resist corrosion.
- Strong Neodymium magnet.

DIMENSIONS



Drawings not to scale.
 All dimensions in inches (mm) nominal.

SPECIFICATION

Dimensions	Length mm	38
	Width mm	10
	Height mm	25
Gauss Strength / Surface	Max	800 (at point A)
Operating Temperature Range	Celsius	-20°C to +85°C
Case Material		Powder Coated Aluminium
Magnet		Neodymium N35

As part of the company policy of continued product improvement, specifications may change without notice. Our sales office will be pleased to help you with the latest information on this product range and the details of our full design and manufacturing service. All products are supplied to our standard conditions of sale unless otherwise agreed in writing.

Phone: (1) 973 777 6900

www.comus-intl.com

Fax: (1) 973 777 8405

Belgium: + 32 (0)12 390400 - Comus Europe Ltd (Assemtech) UK: +44 (0) 1255 862236 - Germany: +49 (0)911 923 15 943 - Netherlands: +31(0)45 54 39 345 - India: +(91) (44) 43219090

©2015 Copyright Comus International, 454 Allwood Road, Clifton NJ 07012, USA