

2:1 Jumbo Reels Heat Shrink

1.2-101.6mm Diameter

Standard: UL 224



• Shrink Ratio:	2:1.
• Material:	Polyolefin - Standard wall heat shrink tube.
• Operating Temperature:	-55°C to +125°C.
• Shrink Properties:	Shrinkable temperature: 80°C.
• Features:	Flame retardant, very good chemical and solvent resistance, excellent electrical and physical properties, anti-static, flexible and high dielectric strength. Chemical resistance: Fuel, hydraulic fluid and lubricating oil.
• Application:	Electrical insulation, cable bundling, pipes and wires giving good physical protection.

PLEASE NOTE: Red Heat Shrink Tubing is NOT Halogen Free



Item No.	Colour	Length (m)	Supplied Internal Diameter Min. (mm)	Recovered Internal Diameter Min. (mm)	Wall Thickness After Recovery (mm)
782-709	Black	300	1.2	0.6	0.36 (±0.10)
782-706	Black	300	1.6	0.8	0.36 (±0.10)
782-700	Black	150	2.4	1.2	0.45 (±0.10)
782-701	Black	150	3.2	1.6	0.45 (±0.10)
782-702	Black	60	4.8	2.4	0.56 (±0.10)
782-703	Black	60	6.4	3.2	0.56 (±0.10)
782-704	Black	60	9.5	4.8	0.56 (±0.10)
782-705	Black	60	12.7	6.4	0.56 (±0.10)
782-710	Black	60	19.1	9.5	0.70 (±0.10)
782-707	Black	30	25.4	12.7	0.90 (±0.15)
782-711	Black	30	38.1	19.1	1.00 (±0.15)
782-712	Black	25	50.8	25.4	1.10 (±0.20)
782-713	Black	25	76.2	38.1	1.46 (±0.20)
782-714	Black	25	101.6	50.8	1.46 (±0.20)