

2:1 Mini Reels Heat Shrink

1.2-25.4mm Diameter

Standard: UL 224



• Shrink Ratio:	2:1.
• Material:	Polyolefin - Standard wall heat shrink tube.
• Operating Temperature:	-55°C to +125°C.
• Shrink Properties:	Shrinkable temperature: 80°C.
• Features:	Flame retardant, very good chemical and solvent resistance, excellent electrical and physical properties, anti-static, flexible and high dielectric strength. Chemical resistance: Fuel, hydraulic fluid and lubricating oil.
• Application:	Electrical insulation, cable bundling, pipes and wires giving good physical protection.



PLEASE NOTE: Red Heat Shrink Tubing is NOT Halogen Free

Item No.	Colour	Length (m)	Supplied Internal Diameter Min. (mm)	Recovered Internal Diameter Min. (mm)	Wall Thickness After Recovery (mm)
782-799	Black	12	1.2	0.6	0.36 (±0.10)
782-810	Black	12	1.6	0.8	0.36 (±0.10)
782-811	Black	11	2.4	1.2	0.45 (±0.10)
782-812	Black	11	3.2	1.6	0.45 (±0.10)
782-813	Black	10	4.8	2.4	0.56 (±0.10)
782-814	Black	9	6.4	3.2	0.56 (±0.10)
782-815	Black	7	9.5	4.8	0.56 (±0.10)
782-816	Black	6	12.7	6.4	0.56 (±0.10)
782-817	Black	5	19.1	9.5	0.70 (±0.10)
782-818	Black	3.5	25.4	12.7	0.90 (±0.15)