

## No 5 TERMINALS (INSULATED)



Also available with twin grip copper sleeve support. When ordering add TG to Part No. i.e DVR 5-4TG.

Conductor Sizes: 2.63–6.64mm<sup>2</sup> 12–10 AWG  
Single Strand: 1.82–2.89 Dia.

### Ring

Yellow Vinyl




Part Number	Dimensions mm			Stud Size mm
	d	D	L	
DVR 5-3	3.2	7.2	20.9	3.0
DVR 5-3.7	3.7	7.2	20.9	3.5
DVR 5-4	4.3	7.2	20.9	4.0
DVR 5-4L	4.3	9.5	25.0	4.0
DVR 5-5	5.3	9.5	25.0	5.0
DVR 5-5L	5.3	12.0	31.0	5.0
DVR 5-6	6.4	12.0	31.0	6.0
DVR 5-6L	6.4	15.0	33.2	6.0
DVR 5-8	8.4	12.0	33.2	8.0
DVR 5-8L	8.4	15.0	33.2	8.0
DVR 5-10	10.5	15.0	33.2	10.0
DVR 5-12	13.0	19.2	37.6	12.0

#### Suitable crimping tools:

DHC 15, DHC 15Y, DHCR 5, DHCR 15, DBMT 1, 3 & 4.

### Pin

Yellow Vinyl



Part Number	Dimensions mm		
	W	D	L
DVP 5-14	2.9	14.0	27.2


#### Suitable crimping tools:

DHC 15, DHC 15Y, DHCR5, DHCR 15, DBMT 1, 3 & 4

For high temperature applications Davico can supply an insulated Makrolon terminal with a working temperature of -40°C to 125°C.

### Fork

Yellow Vinyl



Part Number	Dimensions mm			Stud Size mm
	d	D	L	
DVF 5-3	3.2	8.3	25.2	3.5
DVF 5-4	4.3	8.3	25.2	4.0
DVF 5-4W	4.3	9.0	23.9	4.0
DVF 5-5	5.3	9.0	23.9	5.0
DVF 5-6	6.4	12.0	31.2	6.0

#### Suitable crimping tools:

DHC 15, DHC 15Y, DHCR 5, DHCR 15, DBMT 1, 3 & 4

### Blade

Yellow Vinyl



Part Number	Dimensions mm		
	W	D	L
DVB 5-10	2.8	10.0	20.4
DVB 5-14	4.5	14.0	26.0

### Hooked Blade

Yellow Flared Vinyl



Part Number	Dimensions mm		
	D	W	L
DVB 5-13H	3.0	17.2	30.2
DVB 5-17H	4.6	17.2	30.2

Davico Terminals are designed for easy entry application as indicated.

